



COMMERCIAL PROPULSION ENGINES

CAT - C12

POWER RATING

| | |
|--|--------------------------|
| Power Range | 340-600 bhp (254-448 kW) |
| Continuous Ratings - Maximum Power | 340.0 bhp |
| Heavy Duty Ratings - Maximum Power | 385.0 bhp |
| Maximum Continuous Ratings - Maximum Power | 490.0 bhp |

ENGINE SPECIFICATIONS

| | |
|-------------------------------|---|
| Speed Range | 1800 - 2300 rpm |
| Emissions | EPA Tier 2 Commercial, IMO I, IMO II, EU IW, EU RCD |
| Configuration | In-line 6, 4-Stroke-Cycle Diesel |
| Stroke | 5.9 in |
| Displacement | 732.0 in ³ |
| Rotation (from flywheel end) | Counterclockwise |
| Bore | 5.1 in |
| Aspiration | TA |

DIMENSIONS AND WEIGHTS

| | |
|--------------------|-----------|
| Minimum Dry Weight | 2588.0 lb |
| Maximum Length | 62.0 in |
| Maximum Width | 38.1 in |
| Minimum Height | 39.5 in |
| Minimum Length | 62.0 in |
| Minimum Width | 38.1 in |
| Maximum Height | 39.5 in |