

MARINE GENERATOR SETS

CAT - C18 ACERT TIER 3

GENERATOR SET SPECIFICATIONS

| Minimum Rating | 425 ekW (531 kVA) |
|----------------|-------------------|
| Maximum Rating | 550 ekW (688 kVA) |
| Frequency | 60 Hz |
| Speed | 1800 rpm |

ENGINE SPECIFICATIONS

| In-line 6, 4-Stroke-Cycle Diesel |
|----------------------------------|
| 5.7 in |
| 7.2 in |
| Watercooled Exhaust Manifold a |
| Turbocharger |
| MEUI |
| |

Exhaust Manifold and MEUI

GENERATOR SET CONFIGURATIONS

Emissions - Fuel Strategy

EPA Tier 3, IMO II, EU IW

GENERATOR SET DIMENSIONS

| Weight (estimated) | 4406.0 lb |
|--------------------|-----------|
| Length | 119.7 lb |
| Width | 60.9 in |
| Height | 66.3 |

GENERATOR SPECIFICATIONS

| Excitation | SR4BPermanent Magnet |
|-------------------|------------------------|
| Number of Leads | 12 |
| Insulation | Class H |
| IP - Rating | IP 23 |
| Voltage Regulator | CDVR (Digital Voltage) |